

## Cut resisten - PU, nivel de corte 5

### Descripción

Los guantes Nara Safe – Cut- Pu recubiertos en Poliuretano son de uso industrial para la protección manual de las personas en los diferentes procesos, provee una capa con resistencia al rasgado conforme a la EN388; está fabricado en un material sintético Nylon gris sin costuras. Permite muy buena comodidad, confort, mejor ajuste, mayor destreza y respirabilidad, estas especificaciones se traducen en una mayor productividad para el usuario y durabilidad para el elemento cuando se compara con otros guantes de protección general como los cueros.

### Composición

**Tejido:** Nylon  
**Recubrimiento:** PU. Poliuretano  
**Gauge / Galga # 13**  
**Longitud:** mm 230-250

### Características y usos

#### INFORMACIÓN GENERAL

Puño cerrado en nylon sin costura transpirable, Palma cubierta en nitrilo anti-corte, para mayor destreza y confort del usuario, de tipo multiuso. Ideal para metal metálica, Tienen un tejido de 360° sin costuras que permite que las manos respiren libremente. Nylon dé color gris Gracias a su recubrimiento en poliuretano y su tejido anti-corte tenemos mayor agarre y precisión en las labores a realizar. Recomendado para manipulaciones precisas. Resistente a la abrasión, permitiendo excelente motricidad fina y no trabajar de hidrocarburos, no sumergir.

### Certificaciones y estándares

CE EN388 4543

### Propiedades físicas

Prueba	Nivel
ABRASIÓN	4
CORTE	5
RASGADO	4
PUNZADURA	3

CE EN388



4543

### Presentación

REFERENCIA	TALLA	COLOR BANDA ELÁSTICA	CÓDIGO DE BARRAS
NS2610111	8	Café	4897040905992
NS2610112	9	Blanco	4897040906005
NS2610113	10	Azul	4897040906012

\* Banda elástica color por talla

UNIDAD DE EMPAQUE	12 pares
CAJA MÁSTER	120 unidades
EMPAQUE INDIVIDUAL	Etiqueta de cartón
PESO	50 gr
LONGITUD	240mm - 260mm
COLOR	Gris

#### USOS

Mantenimiento automotriz motos y aeronáuticos  
Manejo de herramientas manual  
Operaciones técnicas de construcción  
Trabajos técnicos de mantenimiento industrial  
Operaciones logísticas  
Empaque y línea de producción  
Imprenta archivo y documentos  
No usar en presencia de hidrocarburos  
Protección al corte





## Cut resisten - PU, nivel de corte 5

### Tablas informativas

CE EN388 Protección mecánica

NIVEL DE ENSAYO	1	2	3	4	5
A. Resistencia a la abrasión (ciclos)	100	500	2000	8000	-----
B. Resistencia al corte (índice)	1.2	2.5	5.0	10.0	20.0
C. Resistencia al rasgado (newton)	10	25	50	75	-----
D. Resistencia a la punzadura (newton)	20	60	100	150	-----

Tallas y medidas

Referencia	S	M	L	XL
Tallas	7	8	9	10
Longitud en mm	230	240	250	260

## Cut resisten - PU, nivel de corte 5 / Certificaciones



In application of the Directive ref. 89/686/EEC of the 21<sup>st</sup> of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29<sup>th</sup> of July 1992 concerning the transposition of this Directive into French law.

### CTC

4, rue Hermann Frenkel - 69367 Cedex 07 - France  
Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupe.com - www.ctc.fr  
Comité Professionnel de Développement Cuir Chaussure Maroquinerie - Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

authorized by decree of the Ministry of Work, Employment and Health of the 20<sup>th</sup> of December 2010,

registered under the number 0075, published in OJEC, delivers :

**CE TYPE EXAMINATION CERTIFICATE**  
**0075/1182/162/09/11/0506**

To the following model of personal protective equipment :

- \* protective glove against mechanical risks.
- \* reference of the model : C1002
- \* responsible for placing on the market :

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

Drawn up in Lyon, on September 16th, 2011

Issued by Lionel GAUDILLERE



4, rue Hermann Frenkel  
69367 Lyon Cedex 07 - France

NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate (change of model, change of manufacturer, change of status) should be brought to the attention of the notified body in accordance with law n° R. 4313-38 of the French Code of Work.

## Cut resiten - PU, nivel de corte 5 / Certificaciones



### 1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index : 01  
Reference : C1002  
Basic Model  
Dated : SEPTEMBER 2011

13 gauge cut-5 liner PU palm coating

#### Available sizes :

7 8 9 10 11

#### Visual description :



#### Material :

	Colour	Material	Gauges	Thikness
PALM	grey	pu	13GAUGE/INCH	
BACK	white/black	UHMWPE YARN	13GAUGE/INCH	
LINING				
CUFF	white/black	UHMWPE YARN	13GAUGE/INCH	
BINDING	blue	polyester		

## Cut resisten - PU, nivel de corte 5 / Certificaciones



### 2. PROTECTION SCOPE

Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:

- \* EN 420:2003+A1:2009 - General requirements for gloves and test methods
- \* EN 388:2003 - Protective glove against mechanical risks
- \* Directive 2002/61/CE : - This product fulfills the requirements given by the Directive.

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	CTC Asia	CTC France	Other
EN 420	SH60641-10 SH60646-10		SH60641-10
Azo	SH60641-10 SH60646-10		
EN 388	SH60641-10 SH61091-10		

Performance levels offered against mechanical risks (EN 388:2003) are:

Abrasion resistance	Blade cut resistance	Tear strength resistance	Puncture resistance
4	5	4	3

The levels of performance have been measured on the palm

## Cut resisten - PU, nivel de corte 5 / Certificaciones



### 3. MARKING

Each glove is clearly marked with the following information:

- Logo of the authorized representative:
- CE marking
- reference of the model: C1002
- size
- pictogram for mechanical risks followed by the performance levels
- information pictogram

Marking example:





## Cut resisten - PU, nivel de corte 5 / Certificaciones

### MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	C1002
Technical file index	:	01
Last update	:	SEPTEMBER 2011



## Cut resisten - PU, nivel de corte 5 / Certificaciones

### IDENTIFICATION

Reference of the product :	:	C1002
Technical file index :	:	01
Last update :	:	SEPTEMBER 2011

**CE Type Examination Applicant :**

**Manufacturer :**



## Cut resisten - PU, nivel de corte 5 / Certificaciones

### GLOVE DESCRIPTION

#### Glove description :

13 gauge cut-5 liner PU palm coating

#### Visual description:



#### Available sizes :

Minimum length of glove (mm)	Sizes
230	7
240	8
250	9
260	10
270	11

#### Glove constitution :

	Reference	Colour	Material	Surfacic mass	Gauges	Thikness
PALM		grey	pu	137g/m2	13GAUGE /INCH	
BACK		white/black	UHMWP E YARN	1235g/m2	13GAUGE /INCH	
LINING						
CUFF		white/black	UHMWP E YARN	1235g/m2	13GAUGE /INCH	
BINDING		blue	polyester			



## Cut resisten - PU, nivel de corte 5 / Certificaciones

### PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

### GENERAL REQUIREMENTS

#### Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5  
PH of glove and lining is greater than 3.5 and lower than 9.5 : yes  
Chromium VI lower than the detection limit : conform  
Size : conform

#### Directive 2002/61/CE :

This product fulfills the requirements given by the Directive 2002/61/CE (Azo dyes).

### SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

#### Mechanical hazard EN 388 : 2003

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	5
Tear strength resistance	4
Puncture resistance	3

## Cut resisten - PU, nivel de corte 5 / Certificaciones

### TEST REPORTS

Laboratory	CTC Asia	CTC France	Other
EN 420	SH60641-10 SH60646-10		SH60641-10
Azo	SH60641-10 SH60646-10		
EN 388	SH60641-10 SH61091-10		

### MARKING - PACKAGING

#### Information printed on the glove :

Logo of the authorized representative :

Logo 

Glove's reference : C1002

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

#### Marking example :



#### Method of marking on the glove :

on the back of the glove

#### Packaging :

12 pairs/polybag, 120 pairs/carton



## Cut resisten - PU, nivel de corte 5 / Certificaciones

### INSTRUCTION FOR USE

Available sizes : 7 8 9 10 11

#### **Glove description :**

13 gauge cut-5 liner PU palm coating

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/1686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (0075)  
4, rue Hermann Frenkel  
69367 LYON Cedex 07  
FRANCE

#### **Applicable standards :**

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :



Application :  
Mechanical hazard - EN 388



4543

Levels of performance

Abrasion resistance	4
Blade cut resistance	5
Tear resistance	4
Puncture resistance	3

#### **Protection limit :**

*The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.*

*This glove shall not be in contact with fire.*

*Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.*

#### **Storage and cleaning notice**

*Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.*